



TECHNICAL DATA

AIRTRONIC – THE RIGHT HEATER FOR EVERY NEED



EBERSPÄCHER AIRTRONIC

Gasoline version	B	Airtronic D2				Airtronic D3*				Airtronic B4			
Diesel version	D												
Voltage	V	12/24				12				12			
Control		low	medium	high	power	low	medium	high	power	low	medium	high	power
Heat output	W	850	1,200	1,800	2,200	900	1,600	2,200	3,000	1,300	2,100	3,200	3,800
Air flow volume	kg/h	40	60	90	105	60	90	120	150	85	120	160	185
Electrical power consumption	W	8	12	22	34	7	10	16	24	9	15	29	40
Fuel consumption	l/h	0.10	0.15	0.23	0.28	0.11	0.20	0.28	0.38	0.18	0.29	0.46	0.54
Dimensions L x W x H	mm	310 x 115 x 122				371 x 140 x 150				371 x 140 x 150			
Weight	kg	2.7				4.5				4.5			



Airtronic D4*				Airtronic D4 Plus*				Airtronic D5*				D8 LC	
12/24				12/24				12/24				12/24	
low	medium	high	power	low	medium	high	power	low	medium	high	power	low	high
900	2,000	3,000	4,000	900	2,000	3,000	4,000	1,600	2,700	4,800	5,500	3,500	8,000
60	120	150	185	55	100	140	185	155	190	275	280	310	310
7	13	24	40	7	16	30	55	25	35	80	85	115	115
0.11	0.25	0.38	0.51	0.11	0.25	0.38	0.51	0.20	0.34	0.58	0.66	0.40	1.05
371 x 140 x 150				371 x 140 x 150				530 x 170 x 185				653 x 260 x 250	
4.5				4.5				9.3				14	

* 100 % biodiesel compatible in accordance with FAME DIN EN 14214.

We are certified in accordance with ISO TS 16949, DIN/ISO 9001 and DIN/ISO 14001.